

MATERIAL SAFETY DATA SHEET

SECTION I		EMERGENCY TELEPHONE NO.
TRADE NAME:	DECO 20 CLEAR PENETRATING CONCRETE SEALER	303-316-4820
CHEMICAL NAME:	REACTED SILICATE	
MANUFACTURER'S NAME:	DECO PRODUCTS, INC.	
ADDRESS:	7900 E. 40 th Ave (City & State)	Denver, CO. (Zip) 80207

SECTION II- HAZARDOUS INGREDIENTS	%	TVL	PE L	UNITS
PRODUCT CONSISTS OF:				
0% V.O.C.				
PROPRIETARY BLEND OF REACTED SILICATE (Non-Hazard)				

SECTION III - PHYSICAL DATA	
Boiling Point (O of F): About 212	Specific Gravity (H 2 0 = 1): 1.1 To 1.3 @ 20 C
Vapor Pressure: / 20 C / 68 F Water	Percent Volatile By Volume : N/A
Vapor Density : N/A	PH: 8.5
Solubility in Water: Excellent	Evaporation Rate: Same As Water
Appearance: Clear	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA	
Flash Point: Not Applicable	Flammable Limits: Not Applicable

SECTION V - HEALTH HAZARD INFORMATION	
Symptoms / Affects of Over Exposure:	
EYES: Slight irritation	
SKIN: Slight irritation	
INHALATION OF VAPOR: Can cause headache, irritation of nose,throat and lungs	
FIRST AID	
Eyes: Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.	
Skin: Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists.	
Inhalation: No TLV, established. Move subject to fresh air.	
Digestion: If swallowed, give 2 glasses of water to drink. Consult a physician. Never give anything by mouth to an unconscious person.	

SECTION VI - REACTIVITY DATA

Stability :	Indefinite at room temperature
Incompatible Materials:	Acid
Hazardous Decomposition Products:	Under fire conditions, alkaline fumes and silica are emitted.

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure:	Ventilate area. Neutralize with acid, absorb onto inert absorbent material and scoop into appropriate container. Rinse area with large volumes of water.
Waste Disposal Method:	Dispose of in accordance with Local, State and Federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory:	Indoors, proper ventilation and goggles
Eye Wear:	Worker goggles
Clothes and gloves:	Wear rubber gloves
Ventilation:	Provide adequate ventilation

SECTION IX - REGULATORY INFORMATION

WORK PLACE CLASSIFICATIONS:	This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR 1910.1200).	
TRANSPORTATION CLASSIFICATIONS:	US DOT Hazard Class	NON-REGULATED
EMERGENCY PLANNING & COMMUNITY RIGHT TO KNOW (SARA TITLE 3)		
Section 311/312 Categorizations (40CFR 370):	This product is not a hazardous chemical under 29CFR 1910.1200 and therefore is not covered by Title III of SARA	
Section 313 Information (40CFR 372):	This product does not contain a chemical which is listed in Section 313 above de minimis concentrations.	
CERCLA INFORMATION (40CFR 302.4):	Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.	
RCRA INFORMATION:	When this product becomes a waste, it is classified as a non-hazardous waste under criteria of the Resource Conservation and Recovery Act (40CFR 261)	
CHEMICAL CONTROL LAW STATUS:	All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.	
STATE RIGHT TO KNOW LAWS:	All material listed as "Not Hazardous" in the CAS REG NO column of COMPONENT INFORMATION Section of this MSDS is trade secret under the provisions of the Worker and Community Right To Know Act.	
STORAGE AND HANDLING INFORMATION:	Keep from freezing. The minimum recommended storage temperature for this material is 1C/34F. The maximum recommended storage temperature for this material is 49C/120F.	

We believe that the information contained in this MSDS sheet is accurate. However, because this material can be used under conditions over which we have no control, we give no warranty, expressed or implied as to the accuracy of the information and assume no responsibility for damage to person, property, or business arising from its use.12/05

WARNING COVER ALL GLASS AND GLAZED TILE SURFACES TO AVOID CONTACT WITH DECO 20 CLEAR PENETRATING CONCRETE SEALER. DECO 20 CAN PERMANENTLY FUSE ITSELF TO THESE MATERIALS.